

# MAE LDV Non-Flameproof Alternator 12V 350W



PART NO: MAEB001225



## • Product Features

- ❖ Non-Flameproof fully sealed unit.
- ❖ Dust proof: IP68
- ❖ 14,2 Volts
- ❖ Max 350W.
- ❖ Max 25A @ 14,2V
- ❖ Brushless.
- ❖ Self-exciting.
- ❖ Cooling system: Thermal conductivity.
- ❖ Various pulley configurations available.

## • Technical Specifications

Max Output Power	350W
Output Voltage	14,2V (12V)
Type	Brushless
Cooling	Thermal Conductivity
Max Alternator Speed	12000 RPM
Weight	10kg
Overall Length	190mm
Overall Diameter	133mm


### NOTE

To request a detailed Technical Specification Datasheet please contact  
[admin@maesa.co.za](mailto:admin@maesa.co.za)


## • Application



LHD LOADER




CONTINUOUS



HAULAGE




LHD DUMP TRUCK




SHUTTLE CAR



GENERAL MINING VEHICLES



DRILLS



LONGWALL SHIELD




## • Summary

The MAE Non Flameproof LDV Alternator 12V 25A is the ideal unit, for all LDV's operating in non-flameproof, underground areas with harsh environment and ambient conditions.

## • Disclaimer

*The information in this specification is derived from the latest model available at the time of issue 1.0. While every precaution has been taken to ensure the accuracy of the content, no responsibility can be accepted for any errors or omissions nor any misinterpretation or misapplication. MAE has adopted a continuous product improvement policy and therefore, specifications are subject to change without prior notice © September 2009 MAE all rights reserved.*

Address: 23 Kemston Avenue  
Benoni  
1501  
Gauteng  
South Africa

Tel: +27 011 421 5551  
Fax: +27 011 421 5618  
Email: [orders@maesa.co.za](mailto:orders@maesa.co.za)  
[admin@maesa.co.za](mailto:admin@maesa.co.za)  
[sales@maesa.co.za](mailto:sales@maesa.co.za)

M-003-25-01

MAE LDV Non-Flameproof Alternator 12V 350W