

MAE Flameproof Alternator 15 Standard 12V 300W

PART NO: MAEF001215



Product Features

- Flameproof & dust proof.
- 12 and 24 Volts configurations available.
- ❖ Max 300W.
- Self-exciting.
- Various pulley configurations available.
- Internal short circuit protection cut-out device.
- Indicator charge pilot light.
- Various cable entries back covers available.
- IA certification.


• Technical Specifications

Max Output Power	300W
Output Voltage	12V
Certificate	M-XPL_15.0216X (IECEX) SIRA 02ATEX1255(ATEX) IP68
Min Alternator Speed	1500 RPM
Max Alternator Speed	12000 RPM
Weight	13kg
Overall Length	258mm
Overall Diameter	133mm

NOTE

To request a detailed Technical Specification Datasheet please contact

admin@maesa.co.za



M-003-15-01

MAE Flameproof Alternator 15 Standard 12V 300W

M-003-15-01-FS-01 16 June 2017 **Page 1 of 2**



Application












LHD LOADER







SHUTTLE CAR



GENERAL MINING VEHICLES

LHD DUMP TRUCK











Summary

The MAE Flameproof Alternator (12V 300W) is compact and robust in design, with low maintenance required and is suitable for hazardous environment zone Ex d I Mb.

This alternator is certified with the following global approvals:

- ❖ ATEX (Europe) SIRA
- ❖ IECEX (South Africa) EXPLOLABS

Disclaimer

The information in this specification is derived from the latest model available at the time of issue 1.0. While every precaution has been taken to ensure the accuracy of the content, no responsibility can be accepted for any errors or omissions nor any misinterpretation or misapplication. MAE has adopted a continuous product improvement policy and therefore, specifications are subject to change without prior notice © September 2009 MAE all rights reserved.

Address: 23 Kemston Avenue,

Benoni 1501 Gauteng South Africa Tel: +27 011 421 5551 Fax: +27 011 421 5618

Email: orders@maesa.co.za admin@maesa.co.za sales@maesa.co.za

M-003-15-01

MAE Flameproof Alternator 15 Standard 12V 300W